

WET WALK BEHIND BLADES

S - STANDARD BLADES are manufactured with high quality diamonds and are designed to be used on low horsepower saws. (.250" diamond height).

S-8 - STANDARD BLADES are manufactured with high quality diamonds and are designed to be used on low horsepower saws. (.300" diamond height).



Cured Concrete		Green Concrete	
C - 02	Hard aggregate — For fast cutting river rock with heavy steel reinforcing	C - 20	Hard aggregate with non-abrasive sand
C - 06	Medium aggregate—For fast cutting slate and glacial rock or limestone with dull sand	C - 40	Hard aggregate or Long life, General Purpose for low horsepower saws
C - 08	Soft aggregate—For fast cutting limestone or other soft materials such as slag	C - 60	Soft to medium aggregate or Long life, General Purpose for high horsepower saws
C - 10	Soft aggregate—For fast cutting soft limestone with sharp sand	C - 68	Limestone or other soft abrasive aggregates
Cured Concrete with Asphalt Overlay		Asphalt	
SS	All Overlay Blades have sweep segments to reduce undercutting	SS	All Asphalt Blades have sweep segments to reduce undercutting
C - 20-SS	Hard aggregate or greater % concrete than asphalt	C - 40 - SS	Hard aggregate
C - 40-SS	Soft to medium aggregate or greater % asphalt than concrete	C - 60 - SS	Soft to medium aggregate
		C - 68 - SS	Limestone or other soft abrasive aggregates

WET WALK BEHIND BLADES

P - PREMIUM BLADES are manufactured with a high concentration of high quality diamonds and are designed to be used on high horsepower saws. (.250" diamond height)

P-8 - PREMIUM PLUS BLADES are manufactured with a high concentration of high quality diamonds and are designed to be used on high horsepower saws. (.300" diamond height)



AVAILABLE SIZES

12" x .125	20" x .218
12" x .145	20" x .250
12" x .160	
12" x .187	24" x .150
12" x .218	24" x .165
12" x .250	24" x .187
12" x .312	24" x .218
12" x .375	24" x .250
12" x .500	
	26" x .165
14" x .125	26" x .187
14" x .145	26" x .218
14" x .160	26" x .250
14" x .187	
14" x .218	28" x .187
14" x .250	28" x .218
14" x .312	28" x .250
14" x .375	
14" x .500	30" x .187
	30" x .218
16" x .125	30" x .250
16" x .145	
	32" x .187
18" x .125	32" x .218
18" x .145	32" x .250
18" x .160	
18" x .187	36" x .187
18" x .218	36" x .218
18" x .250	36" x .250
18" x .375	
18" x .500	42" x .218
	42" x .250
20" x .145	
20" x .160	48" x .218
20" x .187	48" x .250



DROP SEGMENT (DS)

Recommended for mild undercutting applications such as abrasive cured concrete. Sleek sweep segments can be ordered by adding "DS" after the specification.



KICKER SEGMENT (KS)

Recommended for undercutting applications such as very abrasive cured concrete and green concrete. Sleek sweep segments can be ordered by adding "DS" after the specification.



SWEEP SEGMENTS (SS)

Recommended for severe undercutting applications such as asphalt. Sweep segments can be ordered by adding "SS" after the specification.